

NOUVAG⁺

+ SOLUTIONS: MANUFACTURED IN SWITZERLAND +

Suction- and Infiltration pumps

nouvag.com

Vacuson: Precision, Perfection & Reliability

Suction pumps paired with Swiss core values. Robust, highquality suction pumps. Flexible and portable, ideal for use in hospitals, clinics, and medical practices. NOUVAG suction pumps have been designed for a wide range of applications. Choose the optimal pump for your needs with suction capacities ranging from 35 l/min to 70 l/min.

HIGHLIGHTS

- + Maintenance-free, Reliable Technology
- + Consistent Suction Performance Through Powerful Pump Systems
- + Foot Switch Control for Hands-free Operation
- + 2- and 5-litre Polysulfone Secretion Container System
- + Secretion Container System With Disposable Bags
- + Mobile and Flexible With Various Device Trolleys

AREAS OF APPLICATION

- + Liposuction Pump for Subcutaneous Fat Suction
- + Universal Surgery Pump





Vacuson 40 with 35 l/min

+ Economical and versatile

Versatile pump for hospitals and clinics.

The Vacuson 40 is used for suctioning fluids and secretions. The vacuum strength can be continuously adjusted and monitored using the pressure gauge with bar and mmHg scale.

Vacuson 60 with 70 l/min

+ Powerful all-rounder

Whether used for liposuction or other applications, the Vacuson 60 only requires adjusting the vacuum regulator to adapt the suction power to the task at hand. The Vacuson 60 is the perfect pump for use in hospitals and applications where maximum performance is required.

Dispenser DP 30: Reliable Infiltration Pump

The DP 30 dispenser is a universally applicable and controllable infiltration pump that is excellent for the use of tumescent applications in vein treatment.



REF 4186: Dispenser DP 30 with ON-/OFF foot switch

REF 4187: Dispenser DP 30 with VARIO foot switch

HIGHLIGHTS

- + Easy to use, Maintenance-free, and Low Noise
- + Time-saving Compared to Manual Injection of Infiltration Volume
- + Continuously Adjustable and Precise Infiltration Power
- + Adjustable Flow Rate of up to 12.5 l/h (208 ml/min)
- + Can be Operated With Either VARIO or ON/OFF Foot Switch

Dispenser DP 30 LipoPlus: Reliable Infiltration Pump With a Larger Flow Rate



REF 4161: Dispenser DP 30 LipoPlus with ON-/OFF foot switch

REF 4163: Dispenser DP 30 LipoPlus with VARIO foot switch

HIGHLIGHTS

- + Optimized Flow-pressure Ratio for Tumescant Infiltration Prior to Liposuction
- + Low Noise and Maintenance-free
- + Easy Tubing Set Replacement
- + Continuously Adjustable Flow Rate of up to 24 l/h (450 ml/min)
- + Can be Operated With Either VARIO or ON/OFF Foot Switch

Accessories and Secretion Container Systems for Aspiration and Infiltration



REF 4287
Suction jar
2-Litre,
reusable



REF 4288
Suction jar
5-Litre,
reusable



REF 4289
Lid for suction jars
2- and 5-Litre,
reusable



REF 4290
Coupling piece 90°,
reusable
PU: 10 pcs



REF 4291
Suction jar
3-Litre,
reusable



REF 4292
Suction liner
3-Litre,
with solidifying agent
PU: 70 pcs



REF 4130
Suction switch
for switching between
two secretion jars,
including
connecting tubes,
8 x 3 x 400 mm



REF 6022
Disposable tube set
for Dispenser DP 30
and DP 30 LipoPlus
PU: 10 pcs



REF 31717
Clamp holder





REF 6026E

Disposable PVC tube set, 4 metres in length, tube diameter inside/outside: 6.5 / 9.0 mm



REF 4076

Sterilizable silicone tube set, 1.7 metres in length, tube diameter inside/outside: 8.0 / 11.0 mm




REF 4246

Hydrophobic bacteria filter for Vacuson 40 / 60 / 60 LP



REF 4043

Quiver with connecting module for attachment to the hospital rail of the stand



REF 4118

Tube holder for mounting on the stand



Technical Data

Vacuson 40	REF 4227-115 / REF 4227-230
Operating voltage	100 V~ / 115 V~ / 230 V~
switchable	50 – 60 Hz
Power consumption	max. 180 VA (115 V) max. 170 VA (230 V)
Power supply fuse	T4 A (115 V) / T2A (230 V)
Protection class	Class I
Classification of application part	Typ BF (Body Floating)*
Adjustable vacuum	-0.9 bar / 675 mmHG
Suction capacity	35 l/min**
Dimensions (W × D × H)	360 × 300 × 280 mm
Weight	10 kg

Vacuson 60	REF 4237-115 / REF 4237-230
Operating voltage	100 V~ / 115 V~ / 230 V~
switchable	50 – 60 Hz
Power consumption	max. 370 VA (115 V) max. 400 VA (230 V)
Power supply fuse	T4 A (115 V) / T2A (230 V)
Protection class	Class I
Classification of application part	Typ BF (Body Floating)*
Adjustable vacuum	-0.9 bar / 675 mmHG
Suction capacity	70 l/min**
Dimensions (W × D × H)	360 × 300 × 280 mm
Weight	12 kg

* Application parts are instruments used with the device.

** Medium Air.

Dispenser DP 30 LipoPlus	
Operating voltage,	100 V~ / 115 V~ / 230 V~
switchable	50 – 60 Hz
Power consumption	120 VA
Flow rate	0 – 450 ml/min
Weight	3.4 kg

Dispenser DP 30	
Operating voltage,	100 V~ / 115 V~ / 230 V~
switchable	50 – 60 Hz
Power consumption	40 VA
Flow rate	0 – 208 ml/min
Weight	2.4 kg

+ **NOUVAG AG**
St. Gallerstrasse 25
9403 Goldach
Schweiz
T +41 (0) 71 846 66 00
info@nouvag.com

+ **NOUVAG GmbH**
Schulthaißstrasse 15
78462 Konstanz
Deutschland
T +49 (0) 7531 1290-0
F +49 (0) 7531 1290-12
info-de@nouvag.com

NOUVAG⁺